

WPANT30059-RA



Description / Application

This is a high gain Omni-directional antenna that operates in the 2.4 GHz Wi-Fi / WLAN band. It comes with a Type-N female connector. The antenna is at DC ground to ensure protection against lightning.

We can assist your engineers to optimize mounting positions for these antennas in your specific application and can further customize the antennas for your specific needs. Please contact sales@worldproducts.com with your specific application requirements.

Electrical Properties

Operating Frequency	2.4 – 2.5 GHz
Approximate Antenna Impedance [Ω]	50 Ω
VSWR – Typical	< 2:1
Peak Gain [dBi] (Typical)	11 dBi
Polarization	Vertical
Pattern	Omni-Directional
Accepted Power [W] (Max)	200 Watts
Lightning Protection	DC ground

Mechanical / Environmental Properties	
Antenna Dimensions	39.4" (1 meter)
Antenna Color	White
Connector	Type-N Female
Antenna Radome	Fiberglass
Operating / Storage Temperature	-40°C to +90°C
Environmental	Meets standards for UL 94V-0
Hazardous Materials	RoHS Compliant
Note: This antenna will need mounting brackets.	



19654 Eighth Street East P.O. Box 517 Sonoma, CA 95476 (707) 996.5201 www.worldproducts.com sales@worldproducts.com

Pictures of the Antenna

