www.worldproducts.com (707) 996-5201







# MSD Series





Ebusbar established in 2010 with a registered capital of 53 million. It focus on the core components of EV, new energy research and development, production and sales of the national high-tech enterprises. Its products including laminate busbar, EV & PHEV charging connectors, high-voltage electric vehicle connection system, Charging equipment and operation solutions, EV battery Box Solutions, MCU and multi-in-one integrated solutions, HV relays, Depend on a strong R & D and experimental capabilities, advanced and highly efficient manufacturing capabilities. Ebusbar will have to continue to provide our customers professional and innovative solutions, fast and flexible service and high quality products.





# 目录 CONTENTS

# 05 MSD 系列 Series

- 05 维修开关订购信息 MSD Order Information
- 06 MS01维修开关 MS01MSD
- 08 MS02维修开关 MS02 MSD
- 10 MS03 维修开关 MS03 MSD
- 12 MS04 维修开关 MS04 MSD
- 14 MS05维修开关 MS05 MSD




WORLD PRODUCTS INC.® is the Exclusive Agent in North America for Ebusbar® HV Relays for EV.



# MSD SERIES



#### **MSD Series**





# MS01 MSD



#### 规格参数 Specifications:

- 额定电压 Rated Voltage: 700V DC
- 额定电流 Rated Current: 300A Max.
- 工作温度 Temperature Range: -40℃~125℃
- 插拔寿命 Mating Cycles: ≥100
- 高压互锁 HVIL: 有 Yes

- 防护等级 IP Class: IP 67, IP6K9K(Mated)
- 电气保护 Touch Proof: IP2XB
- 阻燃等级 Flame Class: UL94-V0 (Thermoplastic Plastics)
- 熔断器规格 Fuse Specification: 200A / 250A / 350A / 400A/ 500A / 630A

#### 特征和优点 Features and Benefits:

- 延时断开功能 Time delay function
- 特殊端子设计 Special terminal design
- 兼容TE和 Amphenol Compatible with TE and Amphenol

- 前装和后装可选 Front or rear mounting optional
- 定制Fuse, 耐压和过流能力更高 Custom fuse, high voltage and current carrier capacity


# 应 用 Applications:

- PDU, 电池, PEU
- PDU, Battery, PEU




#### ■▶ 插头 Plug:

插头 Plug	高压互锁 HVIL	熔断器型号 Fuse Supplier	熔断器规格 Fuse Specification
			-200
		1 L	-250
			-350
MS01-P	L		-400
			-500
			-630
		0	-000




#### ■▶ 插座-(前安装) Receptacle (Front Mounting):

插座	高压互锁	熔断器型号		栈方式
Receptacle	HVIL	Fuse Supplier		ation Type
MS01-F	L	0	-T02	M8螺纹柱




# ■▶ 插座-(后安装) Receptacle (Rear Mounting):

插座	高压互锁	熔断器型号		栈方式
Receptacle	HVIL	Fuse Supplier		ation Type
MS01-R	L	0	-T02	M8螺纹柱





# MS02 MSD



# 规格参数 Specifications:

- 额定电压 Rated Voltage: 600V DC/700V DC
- 额定电流 Rated Current: 180A Max.
- 工作温度 Temperature Range: -40℃~125℃
- 插拔寿命 Mating Cycles: ≥100
- 高压互锁 HVIL: 有 Yes

- 防护等级 IP Class: IP67(Mated)
- 电气保护 Touch Proof: IP2XB
- 阻燃等级 Flame Class: UL94-V0 (Thermoplastic Plastics)
- 熔断器规格 Fuse Specification: 250A / 315A / 350A / 400A

# 特征和优点 Features and Benefits:

- 产品体积小 Compact size
- 特殊端子设计 Special terminal design
- 兼容TE和 Amphenol Compatible with TE and Amphenol

- 延时断开功能 Time delay function
- 前装和后装可选 Front or rear mounting optional
- 定制Fuse, 耐压和过流能力更高 Custom fuse, high voltage and current carrier capacity

# 应 用 Applications:


● PDU, 电池, PEU

PDU, Battery, PEU



#### ■▶ 插头 Plug:


插头 Plug	高压互锁 HVIL	熔断器型号 Fuse Supplier	熔断器规格 Fuse Specification
			-250
		1	-315
MS02-P	L	L '	-350
			-400
		0	-000



注:熔断器规格: 250A~315A 对应选型电压700V DC, 350A~400A 对应选型电压600V DC Note: When rated current is 250A to 315A ,the corresponding rated voltage is 700V DC. When rated current is 350A to 400A ,the corresponding rated voltage is 600V DC.


#### ■▶ 插座-(前安装) Receptacle (Front Mounting):

插座	高压互锁	熔断器型号		龙方式
Receptacle	HVIL	Fuse Supplier		ation Type
MS02-F	L	0	-T01	M6螺纹柱



#### ■▶ 插座-(后安装) Receptacle (Rear Mounting):

插座	高压互锁	熔断器型号		发方式
Receptacle	HVIL	Fuse Supplier		ation Type
MS02-R	L	0	-T01	M6螺纹柱





# MS03 MSD



# 规格参数 Specifications:

- 额定电压 Rated Voltage: 600V DC/700V DC
- 额定电流 Rated Current: 200A Max.
- T作温度 Temperature Range: -40℃~125℃
- 插拔寿命 Mating Cycles: ≥100
- 高压互锁 HVIL: 有 Yes

- 防护等级 IP Class: IP67(Mated)
- 电气保护 Touch Proof: IP2XB
- 阻燃等级 Flame Class: UL94-V0 (Thermoplastic Plastics)
- 熔断器规格 Fuse Specification: 200A / 250A / 315A / 400A/ 500A / 550A / 630A

#### 特征和优点 Features and Benefits:

- 产品体积小 Compact size
- 多种Fuse规格可用 Multiple fuse available on request
- 转簧端子技术 Consok contact technology

- 助力手柄 Assistance handle
- 内部集成高压互锁功能(可选) HVIL feature (optional)
- 插座尾部多种接线方式,压接、螺纹连接和铜排连接 Can use busbar, crimping, screw connection


# 应 用 Applications:

- PDU, 电池, PEU
- PDU, Battery, PEU



#### ■▶ 插头 Plug:


插头 Plug	高压互锁 HVIL	熔断器型 <del>号</del> Fuse Supplier	熔断器规格 Fuse Specification
		-200	
			-250
	L	L 1	-315
			-350
MS03-P			-400
			-500
			-550
			-630
			-000



Note: When rated current is 200A to 500A , the corresponding rated voltage is 700V DC . When rated current is 550A to 630A , the corresponding rated voltage is 600V DC.


#### ■▶ 插座(前安装) Receptacle (Front Mounting):

插座 Receptacle	高压互锁 HVIL	熔断器型号 Fuse Supplier		栈方式 ation Type
	MS03-F L		-C07	
MS03-F		0	-C08	压接 Crimping
			-C09	
			-T02	螺纹
				-T12
			-H12	尾部过孔 Thread Through Hole



#### ■▶ 插座(小规格)前安装 Receptacle (Small Specification) Front Mounting:

插座 Receptacle	高压互锁 HVIL	熔断器型号 Fuse Supplier		栈方式 ation Type
			-C07	
		L O	-C08	压接 Crimping
MS03-B	L		-C09	Ormiping
			-T02	螺纹
			-T12	Thread
			-H02	尾部过孔
			-H15	Thread Through
			-H25	Hole





# MS04 MSD



# 规格参数 Specifications:

- 额定电压 Rated Voltage: 450V DC
- 额定电流 Rated Current: Based on fuse selection
- 工作温度 Temperature Range: -40℃~125℃
- 插拔寿命 Mating Cycles: ≥100
- 高压互锁 HVIL: 有 Yes

- 防护等级 IP Class: IP67(Mated)
- 电气保护 Touch Proof: IP2XB
- 阻燃等级 Flame Class: UL94-V0 (Thermoplastic Plastics)
- 熔断器规格 Fuse Specification: 250A / 400A

# 特征和优点 Features and Benefits:

- 产品体积小 Compact size
- 多种Fuse规格可用 Multiple fuse available on request
- 转簧端子技术 Consok contact technology

- 助力手柄 Assistance handle
- 内部集成高压互锁功能(可选)HVIL feature (optional)


# 应 用 Applications:

- PDU, 电池, PEU
- PDU, Battery, PEU




#### ■▶ 插头 Plug:

лщ X т rag .			
插头 Plug	高压互锁 HVIL	熔断器型号 Fuse Supplier	熔断器规格 Fuse Specification
MS04-P	L	2	-250
		1	-400



# ■▶ 插座(前安装) Receptacle (Front Mounting):

插座	高压互锁	熔断器型号		龙方式
Receptacle	HVIL	Fuse Supplier		ation Type
MS04-F	L	0	-T02	螺纹 Thread





# MS05 MSD



# 规格参数 Specifications:

- 额定电压 Rated Voltage: 700V DC
- 额定电流 Rated Current: Based on fuse selection
- 工作温度 Temperature Range: -40℃~125℃
- 插拔寿命 Mating Cycles: ≥100
- 高压互锁 HVIL: 无 No

- 防护等级 IP Class: IP67, IP6K9K(Mated)
- 电气保护 Touch Proof: IP2XB
- 阻燃等级 Flame Class: UL94-V0 (Thermoplastic Plastics)
- 熔断器规格 Fuse Specification: 350A / 400A

#### 特征和优点 Features and Benefits:

- 螺丝安装 Screw Installation
- 直流保险丝更高的灭弧功能DC fuse with higher arc extinguishing function
- 10.3mm端子设计 10.3 mm terminal design

◆ 安装方便 Convenient Installation

# 应 用 Applications:


● PDU, 电池, PEU

PDU, Battery, PEU




#### ■▶ 插头 Plug:

лщ X т rag .			
插头 Plug	高压互锁 HVIL	熔断器型号 Fuse Supplier	熔断器规格 Fuse Specification
			-350
MS05-P	N	4	-400
			-000



# ■▶ 插座(前安装) Receptacle (Front Mounting):

插座	高压互锁	熔断器型号	接线方式	
Receptacle	HVIL	Fuse Supplier	Termination Type	
MS05-F	N	0	-T03	M10螺纹柱 Thread





For over 45 years, World Products Inc.® (WPI) has worked with Tier 1 automotive suppliers and has offered the highest quality products with superior technical support to the automotive industry. WPI brings additional value in today's electric vehicle market with our award-winning customer service and a dedicated automotive sales force, while providing our customers with environmentally sound and technologically advanced products. WPI consistently delivers the highest quality products at competitive prices and we support our customers with a world-wide distribution network which assists their businesses to successfully compete in a global market.

World Products Inc.®

19654 Eighth Street East • P.O. Box 517 • Sonoma, CA 95476 • 707.996.5201 www.worldproducts.com • sales@weorldproducts.com

World Products Inc.® is an Employee Owned Company (ESOP)